

## METHOD AND APPARATUS FOR DELIVERING SERVER-ORIGINATED INFORMATION DURING A DORMANT PACKET DATA SESSION

### FIELD

[0001] The present invention relates to point to multi-point communications systems. More specifically, the present invention relates to a method and apparatus for delivering server-originated information to a dormant target communication device in a wireless communication network.

### BACKGROUND

[0002] When the packet data service in a wireless communications system is active, resources in the infrastructure, e.g., base station transceiver subsystem (BTS), base station controller (BSC), interworking (IWF), and the radio link are actively assigned to a mobile station (MS). After a period of inactivity in the communications system, the user traffic channels may transition to the dormant packet data session to conserve system capacity, reduce service cost, and save battery life. However, transitioning a dormant packet data session back to an active session causes a considerable delay in the system response. Existing wireless communication infrastructures provide limited opportunities for significantly reducing the latency in waking up a dormant packet data session, i.e., the actual latency may not be possibly reduced below the time required to re-establish traffic channels within the dormant packet-data session.

[0003] For example, a class of wireless service intended for quick, efficient, one-to-one or one-to-many (group) communication has existed in various forms for many years. In general, these services have been half-duplex, where a user presses a "push-to-talk" (PTT) button on his phone/radio to initiate a call speech. If granted the floor, or talker permission, the user then generally speaks for a few seconds, after which he releases his PTT button, and other speakers can request the floor. Communication is generally from one speaker to a group of listeners, but may be one-to-one. This service has traditionally been used in applications where one person, a "dispatcher," needs to communicate to a group of people, such as field service personnel or taxi drivers, which is where the "dispatch" name for the service comes from. Similar services have been offered on the Internet and are generally known as "voice chat."

[0004] A key feature of these services is that communication is quick and spontaneous, usually initiated by simply pressing a PTT button, without going through a typical dialing and ringing sequence. Communication in this type of service is generally very short, with individual talk "spurts" being generally on the order of several seconds, and "conversations" lasting possibly a minute or less. The time delay between when the user requests the floor and when he receives a

positive or negative confirmation from the server that he has the floor and may begin speaking, which is known as the PTT latency, is a critical parameter for half-duplex group communications systems. As mentioned previously, dispatch systems place a priority on short, quick conversations, which makes the service less effective if the PTT latency becomes large.

[0005] There is a need, therefore, for mechanisms to reduce the latency experienced by the talker and total time required to re-establish traffic channels for participating mobiles without negatively impacting system capacity, client battery life, or other resources.

### SUMMARY

[0006] The disclosed embodiments provide a novel and improved method and apparatus for delivering information to a dormant communication device in a wireless communication network. In one aspect of the invention, a method for delivering information to a dormant target communication device in a wireless communication system, which includes a base station controller (BSC) and a packet control function (PCF), includes receiving information at the BSC for transmission to a target communication device and broadcasting the information to a plurality of communication devices within a service area of the BSC. In one aspect, the information is sent on a reverse access channel (R-ACH) or on a reverse enhanced access channel (R-EACH) as short data bursts.

[0007] In one aspect, a method for delivering information to a dormant target communication device in a wireless communication system, which includes a base station controller (BSC) and a packet control function (PCF), includes receiving information at the BSC for transmission to a target communication device, sending a request to a plurality of communication devices within a service area of the BSC, receiving a response from a communication device in the service area, and sending the information to the communication device that has responded to the request.

[0008] In one aspect, a method for delivering information to a dormant target communication device in a wireless communication system, which includes a plurality of base station controllers (BSCs) in communication with a packet control function (PCF), includes receiving a request at one of the plurality of BSCs to send information to a target communication device, determining if the BSC has location information about the target communication device, and transmitting the information to the target communication device if the BSC has the location information. The method further includes transmitting the information to other BSCs if the BSC does not have location information for the target communication device so that one of the other BSCs that has location information for the target communication device transmits the information to the target communication device. The method further includes broadcasting the information to all

communication devices if none of the BSCs has location information for the target communication device.

[0009] In one aspect, a method for delivering information to a dormant target communication device in a wireless communication system, which includes a mobile station controller (MSC) and a plurality of base station controllers (BSCs) in communication with a packet control function (PCF), includes receiving an application data delivery service (ADDS) page at one of the plurality of BSCs for transmitting information to the target communication device, buffering the information at the BSC, sending a request to a plurality of communication devices within a service area of the BSC, receiving a response from a communication device in the service area, and sending the information to the communication device that has responded to the request.

[0010] In one aspect, an apparatus for delivering information to a dormant target communication device in a wireless communication system includes a memory unit, a receiver, a transmitter, and a processor communicatively coupled with the memory unit, the receiver, and the transmitter. The processor is capable of carrying out the above-mentioned methods.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0011] The features and advantages of the present invention will become more apparent from the detailed description set forth below when taken in conjunction with the drawings in which like reference characters identify correspondingly throughout and wherein:

[0012] FIG. 1 illustrates a group communications system;

[0013] FIG. 2 illustrates how several communication devices interact with a group call server;

[0014] FIG. 3 illustrates an exemplary call-setup process according to one embodiment;

[0015] FIG. 4 illustrates call-signaling details for a network-initiated information delivery process according to one embodiment;

[0016] FIG. 5 illustrates an exemplary process for buffering location information for mobile stations according to one embodiment;

[0017] FIG. 6 illustrates an exemplary configuration for a group communication network according to a first embodiment;

[0018] FIG. 7 illustrates an exemplary configuration for a group communication network according to a second embodiment; and

[0019] FIG. 8 illustrates an exemplary network-initiated information delivery process according to one embodiment.

**DETAILED DESCRIPTION**

[0020] Before one embodiment of the invention is explained in detail, it is to be understood that the invention is not limited in its application to the details of the construction and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is capable of being implemented in other embodiments and are carried out in various ways. Also, it is understood that the phraseology and terminology used herein is for purpose of description and should not be regarded as limiting.

[0021] FIG. 1 illustrates an exemplary functional block diagram of a group communication system 100, for implementing one embodiment of the present invention. The group communication system 100 is also known as a push-to-talk (PTT) system, a net broadcast service (NBS), a dispatch system, or a point-to-multi-point communication system. In one embodiment, the group communication system 100 includes a group call server 102, which may be deployed in either a centralized deployment or a regionalized deployment.

[0022] The group communication devices (clients) 104 and 106, which may be deployed on a cdma2000 handset, for example, may request a packet data session using a data service option and use this session to register its IP address with the application server to perform group call initiations. In one embodiment, group call server 102 is connected to the service provider's packet data service nodes (PDSNs). Clients 104 and 106, upon requesting a packet data session from the wireless infrastructure, may have IP connectivity to the group call server 102 through the PDSNs. The PDSNs provide interfaces between transmission of the data in the fixed network and the transmission of the data over the air interface. Each PDSN may interface to a base station controller (BSC) through a packet control function (PCF) 108, which may be co-located with the BSC within the base station (BS) 110, and the network 112.

[0023] The packet data service may fall in one of several states, e.g., active or connected state, dormant state, and null or inactive state. In the active or connected state, a physical traffic channel exists between the mobile station (MS) and the BS or BSC, and either side may send data. In the dormant state, no physical traffic channel exists between the MS and the BSC, but the PPP link between the MS and the PDSN is maintained. In the null or inactive state, there is no physical traffic channel between the MS and the BSC and no PPP link between the MS and the PDSN.

[0024] Upon power-up, clients 104 and 106 may request a packet data session using the data service option. As part of the establishment of the packet data session, each client may be assigned an IP address. The client 104 and 106 may perform a registration process to notify the group call server 102 of their location information, e.g., IP addresses. The registration may be

performed using an IP protocol, such as session initiation protocol (SIP) over user datagram protocol (UDP). The IP address of the clients may be used to contact the client when the user is invited into a group call.

[0025] Once a group call is established, clients 104 and 106 and group call server 102 may exchange media and signaling messages. In one embodiment, the media may be sent between the call participants and group call server 102 using real-time protocol (RTP) over UDP. The signaling messages may be also signaling protocol over UDP.

[0026] FIG. 2 illustrates an exemplary group 200 for showing how communication devices 202, 204, and 206 interact with a group call server 208. Multiple group call servers may be deployed as desired for large-scale groups. In FIG. 2, CD 202 has permission to transmit media to other members of the group. In this case, CD 202 is known as the talker and transmits media over a channel. When CD 202 is designated as the talker, the remaining participants, CD 204 and CD 206, may not have permission to transmit media to the group. Accordingly, CD 204 and CD 206 are designated as listeners. As described above, CDs 202, 204, and 206 are connected to group call server 208, using at least one channel. In one embodiment, the channel may include a session initiation protocol (SIP) channel, a media-signaling channel, and a media traffic channel.

[0027] The group communication system 100 performs several different functions in order to operate the group services. The functions relating to user experiences include registration, call initiation, call termination, sending alerts, late join, talker arbitration, adding users, removing members, un-registering, addressing, and authentication. The functions relating to system preparation and operation include administration and provisioning, scalability, and reliability. These functions are described in detail in the copending patent application entitled, "A Communication Device for Defining a Group in a Group Communication Network," attorney docket No. PA020042, which is assigned to the same assignee and incorporated herein in its entirety.

[0028] FIG. 3 illustrates an exemplary message flow for starting a group call. The user may be in a dormant packet data session when he or she desires to initiate a group call. The user may select one or more target users, one or more pre-defined groups, or a combination of the two and may depress the push-to-talk (PTT) button. The client may then send a group call request 302 to group call server 102 to setup the group call, regardless of whether the mobile station has a dedicated traffic channel or not, as will be discussed in more detail later. After the request is sent, if the mobile station's packet data session is dormant, the client may initiate the process of re-establishing dedicated traffic channels and preparing the packet data session for media

activity. The client may buffer speech input received from the originator for some period of time.

[0029] When the group call server 102 receives the request, it may expand the pre-defined groups, if any is specified in the request, into target user member lists. Then, the group call server may retrieve the target users' location information. At this point, the group call server may also determine if the desired group is already running in the system. FIG. 3 shows a scenario in which the group is not already running.

[0030] After the group call server locates at least one of the target users, it may send a response 304 back to the client indicating the group call is being set up. At this point, the client may optimistically grant the originator's request to talk and start buffering the received media. The group call server may use the locations of the target users to send out announcements 306 to the target listeners. Sending the announcements may trigger the packet data sessions of the target listeners to come out of dormancy and re-establish their traffic channels.

[0031] The "instant response" relates to the response time it takes for the application server to respond to a PTT or call setup request. The goal for responding to any PTT request, including group call setup requests, is to consistently respond to the request in a predetermined time period, e.g., one second or less. In many cases, when a user requests to setup a group call, the user's packet data session is *dormant* and no dedicated traffic channel exists. Re-establishing dedicated traffic channels may take considerable time. Therefore, communication to the application server may be accomplished through some other means.

[0032] In one embodiment, the group communication system 100 supports both the chat-room model and the ad-hoc model. In the chat-room model, the groups are pre-defined, which may be stored on the dispatch server. The pre-defined groups may be public, implying that the group has an open member list, i.e. any dispatch user is a potential participant. In the chat-room model, the call is started when the first person opts to join the chat-room, and the call remains running, with server resources assigned to the call, regardless of talk activity, for a pre-determined amount of time, which may be configured by the service provider. Users specifically request to join and leave these types of calls. During periods of talk inactivity, each call is brought into a group dormant state, as will be discussed later, until a user requests permission to talk. When operating in the chat-room model in the group communications system 100, a group of communication device users, individually known as net members, communicate with one another using a communication device assigned to each net member. The term "net" denotes a group of communication device users authorized to communicate with each other.

[0033] In the ad-hoc model, groups may be defined in real-time and have a closed member list associated with them. A closed member list may specify which users are allowed to participate in the group, may not be available to users outside of the closed member list, and may only exist for the life of the call. Ad-hoc group definitions may not be stored anywhere; they may be used to establish the call and released after the call has ended. An ad-hoc group may be formed when an originating user selects one or more target users and generates a request, which is sent to a server to start the call. The target users may be sent a notification that they have been included in a group and may automatically be joined into the associated call, i.e., no user action may be required. When an ad-hoc call becomes inactive, the application servers may "tear down" the call and free the resources assigned to it, including the group definition used to start the call.

#### *PTT Latency*

[0034] In one embodiment, when the packet data service is active, resources in the infrastructure, e.g., base station transceiver subsystem (BTS), base station controller (BSC), packet control function (PCF), and the radio link are actively assigned to the mobile station (MS). In an IP-based VoIP dispatch service, while there is an active conversation going on between group participants, the packet data connection for each user remains active. However, after a period of inactivity, i.e., "hang time," in the wireless communications the user traffic channels may transition to the dormant state.

[0035] The transition to the dormant state conserves system capacity and reduces service cost and battery drain. While packet data sessions are active, even if no data packets are being exchanged, radio frequency (RF) energy may still be transmitted by the mobile phones, albeit at a low level, to maintain synchronization and power control with the base station. These transmissions may cause a significant power drain on the phone. In the dormant state, however, the phone may not perform any RF transmission. To conserve phone power and extend battery life, the hang time may be set to transition the phone to dormant mode after extended periods of no data transmission.

[0036] In the exemplary case of group call services, while the packet data service is active for all users, PTT requests, which may be IP datagrams sent between the client CD and the group call server, have very low latency. However, if the user channels have previously transitioned to the dormant state, the PTT latency may be much longer. During packet data dormancy, state information associated with the packet data session, which may include the mobile IP address, may be maintained. However, state information associated with layers below PPP, such as the physical traffic layers, may be released and/or de-allocated.

[0037] In some infrastructures, to wake up a dormant packet data connection, the traffic channel must be reallocated, the resources must be reassigned, and the radio link protocol (RLP) layer must be reinitialized. The effect of this is that after a talk group has not talked for a while, when a user presses his PTT button to request the floor, the PTT latency for the first talk spurt is generally much longer than for subsequent talk spurts. While this is relatively infrequent, it can affect the utility of the service, and should be minimized.

[0038] To reduce the PTT latency, in one embodiment, the group call signaling, such as the floor-control requests, floor-control responses, and dormancy wakeup messages, may be transmitted on some available common channels, without waiting for dedicated traffic channels to be re-established. Such common channels may be always available, regardless of the state of the mobiles, and may not require being requested and reassigned each time a user wishes to initiate a group call. Therefore, the group call signaling may be exchanged even when mobiles are dormant, which may provide a means to re-establish dedicated traffic channels for the talker and listener mobiles in parallel.

[0039] In one embodiment, the calling mobile may send a floor-control request to the wireless infrastructure over some available reverse common channels, such as reverse access channel and reverse enhanced access channel. The calling mobile may also receive a response to the floor-control request on some available forward common channels, such as forward paging channel and forward common control channel. In one embodiment, the dormant listener mobiles may receive dormancy wakeup messages on some available forward common channels, such as forward paging channel and forward common control channel.

#### ***Short Data Burst Call-Signaling Messages***

[0040] In one embodiment, a significant reduction in the actual total dormancy wakeup time may be achieved through the use of the short data burst (SDB) messages, as provided in "TIA/EIA/IS-2000 Standards for cdma2000 Spread Spectrum Systems," hereinafter referred to as "the cdma2000 standard," for example. In one embodiment, SDB messages may be sent over both dedicated physical channels, such as the forward fundamental channel (FCH) or forward dedicated common control channel (F-DCCH), or common physical channels, such as the reverse access channel (R-ACH), reverse enhanced access channel (R-EACH), forward common control channel (F-CCCH), or paging channel (PCH). The SDB messages may be transported by radio burst protocol (RBP), which maps the messages onto an appropriate and available physical layer channel. Because SDB messages may carry arbitrary IP traffic and may be sent over common



physical channels, SDB messages provide a mechanism to exchange group call signaling when a calling client's mobile has no dedicated traffic channels.

### ***Mobile-Originated Call-Signaling Messages***

[0041] In one embodiment, media-signaling messages may carry IP datagrams over the reverse link or mobile-originated link. A client mobile station may signal the group call server quickly whenever the user requests the floor and a dedicated reverse traffic channel is not immediately available. Assuming the client mobile station has released all dedicated traffic channels, the client mobile station may immediately forward the floor-control request over a reverse common channel of a wireless infrastructure, which may relay the request to the group call server. For example, either the reverse access channel or the reverse enhanced access channel may be used to send such messages when a dedicated reverse channel is not available. In one embodiment, the client mobile station may transmit a floor-request message to the group call server as an SDB Message.

### ***Network-Originated Call-Signaling Messages***

[0042] In one embodiment, after receiving the floor-control request, the group call server may burst media signaling messages to a group of target participants (listeners) and trigger the re-establishment of participants' (listeners') traffic channels. In one embodiment, when the packet control function (PCF) receives a small amount of information, e.g., packet data, from the packet data serving node (PDSN), which may be destined for a mobile with the dormant packet data service instance, the PCF may choose to send the information to the base station controller (BSC) in a special form. In one embodiment, the special form includes short data burst (SDB) format, as specified in the TIA/EIA/IS-707-A-2, "Data Service Option Standard for Spread Spectrum Systems", Addendum 2, dated June 2000 (IS-707-A-2). The TIA/EIA/IS-2001-A, "Interoperability Specification (IOS) for cdma2000 Access Network Interfaces," dated August 2001, (IS-2001-A) standard defines several options for the BSC to deliver the SDB to the mobile.

[0043] According to the IS-2001-A standard, for example, when a small amount of data destined for a dormant packet data service instance on a mobile is received at the PCF, the PCF may choose to send this data to the BSC in SDB format. If the BSC determines that short data bursts may be used to deliver the data to the mobile, the BSC may send the data, which may be in SDB format, directly to the mobile over the signaling channel. The BSC may also send this data, in SDB format, to the MSC for delivery to the mobile via the application data delivery service (ADDS) page. The data may be delivered to the MSC using the BSC service request/response

procedure. If the BSC is unsuccessful in delivering the SDB data to the mobile on its own, it may choose to send the data to the MSC for delivery to the mobile via the ADDS page procedure.

[0044] An exemplary call-flow procedure for the mobile-terminated SDB delivery is shown in FIG. 4, as described in IS-2001-A standard.

[0045] In one embodiment, the packet data is in the dormant state 402, with PPP connected. The PDSN may send 404 packet data to the PCF on the existing PPP connection, e.g. A10 connection, associated with a specific mobile. The PCF may send 406 the packet data to the BSC, e.g. in short data bursts on an A9 connection. The PCF may also buffer the packet data.

[0046] The BSC may acknowledge the receipt of the A9-SDB message from the PCF by returning 408 an, e.g., A9-SDB, acknowledge message, which may include an indication that the BSC may attempt to send the data to the mobile as a SDB. The PCF may then discard the data that it had buffered.

[0047] The BSC may send the packet data, e.g., in SDB form, directly to the mobile, or alternatively the BSC may use the ADDS page procedure. The BSC may decide to deliver the data to the mobile over the traffic channel by first bringing up the traffic channel. If the BSC directly sends 410 the SDB to the mobile, the mobile may send 412, e.g., a layer 2, acknowledgement in response to the SDB received from the BSC. If the acknowledgement is not received from the mobile, the BSC may choose not to send the data or may rely on the MSC to deliver the data via ADDS Page procedure.

[0048] If the BSC could not successfully send the SDB to the mobile in step 410, the BSC may send 414 the SDB data to the MSC in a BSC service request message. The MSC may acknowledge the reception of the BSC service request message by sending 416 a BSC service response to the BSC. The MSC may send 418 an ADDS Page message to the BSC(s) with the data burst type field in the ADDS user part element set to SDB, and the SDB included in the application data message field. The BSC may forward 420 the SDB to the mobile. An, e.g., layer 2, acknowledgement may be sent 422 by the mobile after receiving the SDB from the BSC.

[0049] If the MSC had included a tag element in the ADDS page message, the BSC may return 424 an ADDS page acknowledge message to the MSC after receiving the acknowledge 422 from the mobile. The BSC may send 426 an, e.g., A9-update-A8, message to the PCF to indicate successful transmission of the SDB to the mobile. The PCF may send 428 an, e.g., A11, registration request with the SDB airlink record to the PDSN. The PDSN may respond 430 with an, e.g., A11, registration reply message. The PCF may respond 432 to the BSC with an, e.g., A9, update acknowledge.

[0050] Having the BSC directly deliver the SDB to the mobile may minimize the delay, but the mobile may not receive the SDB because it may have moved out of the BSC service area by the time the SDB arrives. Since the MSC maintains mobile location information, ADDS Page ensures that the mobile receives the SDB. However, this procedure may incur a larger delay, since the BSC has to send the SDB to the MSC first, and then the MSC sends the SDB to the appropriate BSCs to perform the ADDS Page.

### ***Caching Mobile's Location***

[0051] In one embodiment, the BSC may cache the mobile's location information, which may be used by the BSC when there is a SDB destined for the mobile and the packet data session is dormant. Using the cached mobile location information eliminates the delay due to MSC's sending the ADDS Page and provides assured delivery of the SDB to the mobile.

[0052] In one embodiment, the BSC may obtain the location information of the target mobile from the mobile's response to the page request sent by the MSC. The page response message may include a cell identifier field that specifies the location, e.g., a cell location area code (LAC), of the mobile. In one embodiment, the BSC may obtain the location information from the mobile's registration message. There are several different types of registration defined by the TIA/EIA/IS-2000.5-A, "Upper Layer (Layer 3) Signaling Standard for cdma2000 Spread Spectrum Systems," dated November 2000, (IS-2000 standard), for example. Any of these registration types may provide the BSC information about the location of the mobile. The BSC may update its cached database if it receives a page response, a registration response, an origination message, or other signaling messages that provide the location information for the mobile.

[0053] As illustrated in FIG. 5, the BSC may cache 502, 504 the mobile's location information after it receives 506 an, e.g., IS-2000, page response from the mobile or receives 508 the location information update accept message from the MSC. A cache timer may be set according to the frequency of the mobile's location update via the registration message.

### ***Network Configurations***

[0054] Each PCF in the network may be uniquely identified by system identification/network identification/packet zone identification (SID/NID/PZID). When the mobile moves from one PCF to another PCF, i.e., PCF to PCF handoff, during the dormant packet data session, the mobile may be required to reregister to have the PDSN establish an, e.g., A10/A11, interface with the new PCF and terminate the existing connection with the old PCF.

[0055] In one embodiment, as shown in FIG. 6, the BSC and the PCF are co-located. When the packet data arrives at the PCF through an, e.g., A10/A11, connection, and the PCF decides to send packet data as a SDB, the mobile may most probably be under the same BSC service area; otherwise, the mobile would have required to re-register and a new, e.g., A10/A11, connection would have been established to a different PCF.

[0056] In one embodiment, as shown in FIG. 7, the BSC and the PCF are not co-located. The BSCs and PCF may be interfaced via the A8/A10 connections, for example. The BSCs may interface with each other via the A3/A7 connections, for example. In FIG. 7, BSC<sub>1</sub> is shown to be fully interconnected with other BSCs that are connected to the same PCF. The BSCs that are connected to the same PCF may be interconnected either via point-to-point link or via a switching network. Unlike the scenario where the BSC and the PCF are co-located, when the PCF sends the SDB to the BSC<sub>1</sub>, BSC<sub>1</sub> may fail in delivering the SDB to the target mobile because the target mobile may have moved outside the BSC<sub>1</sub> area to another BSC service area. In FIG. 7, for example, the mobile may had been in the BSC<sub>1</sub> before the packet data session goes dormant and may have moved to BSC<sub>5</sub> when the BSC<sub>1</sub> receives the request from the PCF for SDB delivery.

[0057] In a first embodiment, where the PCF may be co-located with the BSC, the PCF/BSC may send the information to target mobiles as a SDB, by broadcasting the SDB to all cells within the BSC's service area. Alternatively, to decrease the air link resource consumption, the BSC may utilize the mobile's location information, which may have been already cached at the BSC, to broadcast the data burst to a subset of cells under its control.

[0058] In a second embodiment, where the PCF may be co-located with the BSC, as shown in FIG. 8, upon reception 802 of the packet data from the PDSN, before the BSC/PCF sends the information to a target mobile as a SDB, the BSC/PCF may first buffer the information. The BSC/PCF then sends out 804 a request, e.g. an IS-2000 registration request, a page, or other signaling messages, to all or a subset of the cells under its service area based on the BSC's cached mobile's location information. The mobile with some identification information, such as the matching mobile identification number (MIN) or electronic serial number (ESN), responses to the registration request message by sending 806 a response, e.g., a registration message response or a general page response. The response may provide information of which cell/sector the mobile is located in, which allows the BSC to send the information to the destined cell/sector only. The BSC may cache 808 the mobile's location information before sending 810 the SDB to the target mobile. The cached location information may be refreshed by the next page response,

registration response, origination message, or other signaling messages that provide the location information for the mobile, or aged out by a timer.

[0059] In a third embodiment, where the PCF may not be co-located with the BSC, after the reception of the PCF request to send the information, e.g., as IS-2000 short data bursts, the BSC may determine if it has cached location information for the target mobile. If the location information is cached, which allows the BSC to perform assured delivery, the BSC may send the SDB as short data bursts to a set of cells according to the cached location information. Alternatively, the BSC may send the SDB received from the PCF to other BSCs, which may be connected to the same PCF, e.g., via the A3/A7 connections. The BSCs that have cached information of the target mobile may deliver the SDB as data bursts to those cells based on the cached location information. The BSCs that have not cached location information may also broadcast the data bursts to all cells under their service areas.

[0060] In a fourth embodiment, where the PCF may not be co-located with the BSC, instead of directly sending the information, e.g., as SDB, when the BSC receives the information from another BSC or PCF, the BSC may first buffer the SDB and send out a request, as described above in connection with FIG. 8. After receiving a corresponding response from the mobile, the information, e.g., in data burst, may be sent only to the cell or sector identified in the mobile's registration message. Alternatively, the BSC may utilize the cached information of the mobile location to send the request only to a subset of cells serviced by the BSC.

[0061] According to a fifth embodiment, where the PCF may not be co-located with the BSC, the BSC may use a registration request or a general page to improve the bandwidth efficiency. When the BSC receives an ADDS Page message from the MSC, instead of broadcasting the information, e.g., in SDB form, to a set of cells as specified in the MSC ADDS page message, the BSC may first buffer the information and then send out a request, e.g., a registration request, a page, or other signaling messages, as discussed in connection with FIG. 8. After receiving a response, e.g., a registration message response or a general page response, from the mobile, the information may be then sent only to the sector or cell identified by the received response. Alternatively, the BSC may utilize the cached location information of the mobile location to send the request to only a subset of cells serviced by the BSC.

[0062] Therefore, disclosed embodiments provide for a significant reduction in the actual total dormancy wakeup time by exchanging call signaling even when the mobiles are dormant and no traffic channel is active. The method and apparatus provides for exchanging the group call signaling through the use of the short data burst (SDB) message signaling.

[0063] Although several embodiments of the invention is explained in connection with some exemplary group call services, it is to be understood that the invention is not limited in its application to the details of the construction and the arrangement of the components set forth in the disclosed description or illustrated in the drawings. The invention is capable of being implemented in other embodiments and carried out in various ways, for example, in an instant messaging service or any general wireless data communication applications.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
22